## PART NUMBER CONFIGURATION

VNC A060 - F - WKCS - NN - T - RN 30 - L - K A N E

*Complete Meter*

| **VN2000 Compact Insertion Vortex Meter Kit** | VNC | | - | | - | | - | | | - | | | - | | | - | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Pipe Line Size**[1] | | | | | | | | | | | | | | | | | | | | |
| 2 inch | | A020 | | | | | | | | | | | | | | | | | | |
| 3 inch | | A030 | | | | | | | | | | | | | | | | | | |
| 4 inch | | A040 | | | | | | | | | | | | | | | | | | |
| 6 inch | | A060 | | | | | | | | | | | | | | | | | | |
| 8 inch | | A080 | | | | | | | | | | | | | | | | | | |
| 10 inch | | A100 | | | | | | | | | | | | | | | | | | |
| 12 inch | | A120 | | | | | | | | | | | | | | | | | | |
| 14 inch | | A140 | | | | | | | | | | | | | | | | | | |
| 16 inch | | A160 | | | | | | | | | | | | | | | | | | |
| 18 inch | | A180 | | | | | | | | | | | | | | | | | | |
| 20 inch | | A200 | | | | | | | | | | | | | | | | | | |
| 22 inch | | A220 | | | | | | | | | | | | | | | | | | |
| 24 inch | | A240 | | | | | | | | | | | | | | | | | | |
| **Material** | | | | | | | | | | | | | | | | | | | | |
| 304L Stainless Steel | | | | F | | | | | | | | | | | | | | | | |
| **Mounting Assembly Kit** | | | | | | | | | | | | | | | | | | | | |
| 1-1/2 inch Carbon Steel | | | | | | WKCS | | | | | | | | | | | | | | |
| **Process Temperature & Pressure** Standard Temperature, Standard Pressure | | | | | | | | N | | | | | | | | | | | | |
| **Reserved** | | | | | | | | | | | | | | | | | | | | |
| None | | | | | | | | | N | | | | | | | | | | | |
| **Measurements & Calculations** | | | | | | | | | | | | | | | | | | | | |
| Volumetric flow rate only | | | | | | | | | | V | | | | | | | | | | |
| Mass flow based on velocity and internal temperatur | | | | | | | | | | T | | | | | | | | | | |
| Heat energy/BTU based on velocity and temperature | | | | | | | | | | E | | | | | | | | | | |
| **Transmitter Type** | | | | | | | | | | | | | | | | | | | | |
| Integral, 24V DC | | | | | | | | | | | MN | | | | | | | | | |
| Remote, 24V DC | | | | | | | | | | | RN | | | | | | | | | |
| **Cable Length** | | | | | | | | | | | | | | | | | | | | |
| None (integral meter mount only) | | | | | | | | | | | | 00 | | | | | | | | |
| 9 feet (remote only) | | | | | | | | | | | | 09 | | | | | | | | |
| 30 feet (remote only) | | | | | | | | | | | | 30 | | | | | | | | |
| **Fluid** | | | | | | | | | | | | | | | | | | | | |
| Liquid | | | | | | | | | | | | | | L | | | | | | |
| Gas | | | | | | | | | | | | | | G | | | | | | |
| Steam | | | | | | | | | | | | | | S | | | | | | |
| **Display** | | | | | | | | | | | | | | | | | | | | |
| Display and keypad | | | | | | | | | | | | | | | | K | | | | |
| **Communication & I/O** | | | | | | | | | | | | | | | | | | | | |
| 4…20 mA and pulse | | | | | | | | | | | | | | | | | A | | | |
| Modbus RTU RS485 | | | | | | | | | | | | | | | | | M | | | |
| **Reserved** | | | | | | | | | | | | | | | | | | | | |
| None | | | | | | | | | | | | | | | | | | N | | |
| **Language** | | | | | | | | | | | | | | | | | | | | |
| English | | | | | | | | | | | | | | | | | | | E | |

Preliminary Draft